


# MK-3320E / MK-3320C B/W DOME CAMERA

## INSTRUCTION

Dimension: Unit (mm)



## SPECIFICATION

MODEL NO.	MK-3320E	MK-3320C
IMAGE SENSOR DEVICE	1/3" interline transfer CCD	
IMAGE SENSOR AREA	4.8mm x 3.6mm	
HORIZONTAL FREQUENCY	15.734KHz	15.625KHz
VERTICAL FREQUENCY	59.9Hz	50Hz
TOTAL PIXELS	542(H) x 492(V)	542(H) x 582(V)
SCANNING SYSTEM	525 lines, 60 fields/sec EIA	625 lines, 50 fields/sec CCIR
RESOLUTION	420 TV lines horizontal	
MINIMUM ILLUMINATION	0.5 lux at F2.0	
ELECTRONIC SHUTTER	Auto electronic shutter 1/60 - 1/100000 sec. continual	Auto electronic shutter 1/50 - 1/100000 sec. continual
S/N RATIO	Better than 45 dB	
VIDEO SIGNAL OUTPUT	1.0Vp-p composite video signal at 75 ohm load	
GAMMA CORRECTION	0.45	
GAIN CONTROL	Auto Gain Control	
POWER SUPPLY	12V DC $\pm 10\%$ / 1.2W	
LENS & VIEW ANGLE	3.6mm F2.0 / 92°	
OPERATING TEMPERATURE	-20°C to 55°C	
OPERATING HUMIDITY	within 85% RH	
DIMENSIONS & WEIGHT	88(H) x 60(D) mm / 100g	
SCANNING SYSTEM	INTERLACE / NON-INTERLACE SWITCHABLE ON BOARD	

\* The specifications and appearance of the product may changed without notice.