

LOW DROP OUT VOLTAGE REGULATOR

参考資料

■ GENERAL DESCRIPTION

The NJM2930 3-terminal positive voltage regulator features an ability to source 150mA of output current (100mA: L-Type) with an input-output differential of 0.6V or less. Efficient use of low input voltages obtained, for example, from an automotive battery during cold crank conditions, allows 5V circuitry to be properly powered with supply voltages as low as 5.6V.


Familiar regulator features such as current limit and thermal overload protection are also provided.

■ FEATURES

- Operating Voltage
- Input-Output differential less 0.6V
- Output Current in Excess of 150mA
- 40V Load Dump Protection
- Internal Short Circuit Current Limit
- Internal Thermal Overload Protection
- Package Outline TO-220F, TO-92
- Bipolar Technology


■ PACKAGE OUTLINE

(TO-220F)



NJM2930F

(TO-92)




NJM2930L

1. Input
2. GND
3. Output

1. Output
2. GND
3. Input

■ EQUIVALENT CIRCUIT



6

■ ABSOLUTE MAXIMUM RATINGS

(Ta=25°C)

PARAMETER	SYMBOL	RATINGS	UNIT
Operating Input Voltage Range	V _{IN}	26	V
Input Overvoltage Protection	V _{PR}	40	V
Input Reverse Voltage	V _{INR1} (100ms)	-12	V
Input Reverse Voltage	V _{INR2} (DC)	-6	V
Maximum Output Current	I _{OM}	(TO-92) 100	mA
		(TO-220F) 150	mA
Power Dissipation	P _D	(TO-92) 500	mW
		(TO-220F) 7.5(Note)	W
Operating Temperature Range	T _{opr}	-30~75	°C
Storage Temperature Range	T _{stg}	-40~125	°C

(note) Case Temperature : T_{case} ≤ 75°C, Thermal Resistance: θ_{je} = 5°C/W TYP.

■ ELECTRICAL CHARACTERISTICS

(All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques.)

NJM2930F05 (V_{IN}=14V, C₂=10μF, T_J=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Output Voltage	V _O	6V ≤ V _{IN} ≤ 26V, 5mA ≤ I _O ≤ 100mA	4.5	5	5.5	V
Line Regulation	ΔV _O -V _I	9V ≤ V _{IN} ≤ 16V, I _O = 5mA	—	7	25	mV
		6V ≤ V _{IN} ≤ 26V, I _O = 5mA	—	30	80	mV
Load Regulation	ΔV _O -I _O	5mA ≤ I _O ≤ 150mA	—	14	50	mV
Quiescent Current	I _{Q1}	I _O = 10mA	—	4	7	mA
		I _O = 150mA	—	30	40	mA
Dropout Voltage	ΔV _I -O	I _O = 150mA	—	0.3	0.6	V
Output Noise Voltage	V _{NO}	10Hz~100kHz, I _O = 150mA	—	100	—	μV
Ripple Rejection	RR	f = 120Hz, I _O = 150mA	—	60	—	dB

NJM2930L 05 (V_{IN}=14V, C₂=10μF, T_J=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Output Voltage	V _O	6V ≤ V _{IN} ≤ 26V, 5mA ≤ I _O ≤ 100mA	4.5	5	5.5	V
Line Regulation	ΔV _O -V _I	9V ≤ V _{IN} ≤ 16V, I _O = 5mA	—	7	25	mV
		6V ≤ V _{IN} ≤ 26V, I _O = 5mA	—	30	80	mV
Load Regulation	ΔV _O -I _O	5mA ≤ I _O ≤ 100mA	—	14	50	mV
Quiescent Current	I _{Q1}	I _O = 10mA	—	4	7	mA
		I _O = 100mA	—	25	40	mA
Dropout Voltage	ΔV _I -O	I _O = 100mA	—	0.25	0.6	V
Output Noise Voltage	V _{NO}	10Hz~100kHz, I _O = 40mA, V _{IN} = 10V	—	100	—	μV
Ripple Rejection	RR	f = 120Hz, I _O = 40mA, V _{IN}	—	60	—	dB

NJM2930F08 ($V_{IN}=14V$, $C_2=10\mu F$, $T_j=25^\circ C$)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Output Voltage	V_O	$9.4V \leq V_{IN} \leq 26V$, $5mA \leq I_O \leq 150mA$	7.2	8	8.8	V
Line Regulation	$\Delta V_O - V_I$	$9.4V \leq V_{IN} \leq 16V$, $I_O = 5mA$	—	12	50	mV
	$\Delta V_O - V_I$	$9.4V \leq V_{IN} \leq 26V$, $I_O = 5mA$	—	50	100	mV
Load Regulation	$\Delta V_O - I_O$	$5mA \leq I_O \leq 150mA$	—	25	50	mV
Quiescent Current	I_{Q1}	$I_O = 10mA$	—	4	7	mA
	I_{Q2}	$I_O = 150mA$	—	30	40	mA
Dropout Voltage	ΔV_{1-o}	$I_O = 150mA$	—	0.3	0.6	V
Output Noise Voltage	V_{NO}	10Hz~100kHz, $I_O = 150mA$	—	140	—	μV
Ripple Rejection	RR	$f=120Hz$, $I_O = 150mA$	—	57	—	dB

NJM2930L 08 ($V_{IN}=14V$, $C_2=10\mu F$, $T_j=25^\circ C$)

PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Output Voltage	V_O	$9.4V \leq V_{IN} \leq 26V$, $5mA \leq I_O \leq 100mA$	7.2	8	8.8	V
Line Regulation	$\Delta V_O - V_I$	$9.4V \leq V_{IN} \leq 16V$, $I_O = 5mA$	—	12	50	mV
	$\Delta V_O - V_I$	$9.4V \leq V_{IN} \leq 26V$, $I_O = 5mA$	—	50	100	mV
Load Regulation	$\Delta V_O - I_O$	$5mA \leq I_O \leq 100mA$	—	25	50	mV
Quiescent Current	I_{Q1}	$I_O = 10mA$	—	4	7	mA
	I_{Q2}	$I_O = 100mA$	—	25	40	mA
Dropout Voltage	ΔV_{1-o}	$I_O = 100mA$	—	0.25	0.6	V
Output Noise Voltage	V_{NO}	10Hz~100kHz, $I_O = 40mA$	—	140	—	μV
Ripple Rejection	RR	$f=120Hz$, $I_O = 40mA$	—	57	—	dB

NJM2930F85 ($V_{IN}=14V$, $C_2=10\mu F$, $T_j=25^\circ C$)


PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Output Voltage	V_O	$9.95V \leq V_{IN} \leq 26V$, $5mA \leq I_O \leq 150mA$	7.65	8.5	9.35	V
Line Regulation	$\Delta V_O - V_I$	$9.95V \leq V_{IN} \leq 16V$, $I_O = 5mA$	—	12	50	mV
	$\Delta V_O - V_I$	$9.95V \leq V_{IN} \leq 26V$, $I_O = 5mA$	—	50	100	mV
Load Regulation	$\Delta V_O - I_O$	$5mA \leq I_O \leq 150mA$	—	25	50	mV
Quiescent Current	I_{Q1}	$I_O = 10mA$	—	4	7	mA
	I_{Q2}	$I_O = 150mA$	—	30	40	mA
Dropout Voltage	ΔV_{1-o}	$I_O = 150mA$	—	0.3	0.6	V
Output Noise Voltage	V_{NO}	10Hz~100kHz, $I_O = 150mA$	—	150	—	μV
Ripple Rejection	RR	$f=120Hz$, $I_O = 150mA$	—	56	—	dB

NJM2930L 85 ($V_{IN}=14V$, $C_2=10\mu F$, $T_j=25^\circ C$)



PARAMETER	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Output Voltage	V_O	$9.95V \leq V_{IN} \leq 26V$, $5mA \leq I_O \leq 100mA$	7.65	8.5	9.35	V
Line Regulation	$\Delta V_O - V_I$	$9.95V \leq V_{IN} \leq 16V$, $I_O = 5mA$	—	12	50	mV
	$\Delta V_O - V_I$	$9.4V \leq V_{IN} \leq 26V$, $I_O = 5mA$	—	50	100	mV
Load Regulation	$\Delta V_O - I_O$	$5mA \leq I_O \leq 100mA$	—	25	50	mV
Quiescent Current	I_{Q1}	$I_O = 10mA$	—	4	7	mA
	I_{Q2}	$I_O = 100mA$	—	25	40	mA
Dropout Voltage	ΔV_{1-o}	$I_O = 100mA$	—	0.25	0.6	V
Output Noise Voltage	V_{NO}	10Hz~100kHz, $I_O = 40mA$	—	150	—	μV
Ripple Rejection	RR	$f=120Hz$, $I_O = 40mA$	—	56	—	dB

■ STANDARD APPLICATION EXAMPLES

- * This NJM2930 is required when the mounting position is separated from the power filter.
- ** Use an aluminum electrolytic capacitor or a tantalum capacitor as C_2 . The temperature guarantee range of capacitors should be down to -30°C . A capacity value of $10\mu\text{F}$ is a minimum requirement for improving the stability and transient response. Mount it at a position as close to the leads as possible.
- *** When application on automobile car operation, the minus pulse might be input on IC. In this case, however, the pulse might trigger to latch up. If it were that, this kind of latching up might be continued, the IC would burn up into defective in many cases. It is advisable to apply D1, D2 as described in the drawing, in order to prevent from making any troubles. It is important to make devices D1, D2 against V_{IN} to be able to stand for brake down voltage, current volume, and then less volume for V_{f} .




■ POWER DISSIPATION VS. AMBIENT TEMPERATURE




TYPICAL CHARACTERISTICS


NJM2930F05/L05 Output Voltage
($T_j=25^\circ\text{C}$, $I_o=0\text{mA}$)




NJM2930F05/L05 $I_{CC}-V_{IN}$
($T_j=25^\circ\text{C}$, $I_o=0\text{mA}$)




NJM2939F05/L05 Thermal Shutdown
($V_{IN}=14\text{V}$, $I_o=50\text{mA}$)




NJM2930F05/L05 Load Characteristics
($V_{IN}=14\text{V}$, $T_j=25^\circ\text{C}$)



NJM2930L05 Output Current vs. Quiescent Current
($V_{IN}=14\text{V}$, $T_j=25^\circ\text{C}$)



NJM2930F05 Output Current vs. Quiescent Current
($V_{IN}=14\text{V}$, $T_j=25^\circ\text{C}$)




6

■ TYPICAL CHARACTERISTICS


NJM2930F05/L05 Ripple Rejection vs. Frequency

($T_a=25^\circ\text{C}$, $V_{IN}=14\text{V}$, $I_o=40\text{mA}$, $e_{in}=2\text{V}_{P-P}$)




NJM2930F05/L05 Output Voltage

($V_{IN}=14\text{V}$, $I_o=1\text{mA}$)




NJM2930L05 Dropout Voltage

($T_j=25^\circ\text{C}$)




NJM2930F05 Dropout Voltage

($T_j=25^\circ\text{C}$)



NJM2930F05 Dropout Voltage vs. Output Current

($T_j=25^\circ\text{C}$)



MEMO

[CAUTION]

The specifications on this databook are only given for information, without any guarantee as regards either mistakes or omissions. The application circuits in this databook are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.